

Series 3500

- Fuel Dispensing (Consult Factory)
- Bulk Transfer
- Fire Protection

To handle 1" through 1-3/4" I.D. hose.

- Economical manual rewind reels for long lengths of hose.
- Choose disc rewind or removable direct crank rewind.
- Supplied with spring actuated pin lock.
- Standard inlet: 90° swivel joint, 1-1/2" female NPT threads, and 2" victaulic groove.
- Standard outlet: flanged riser with 1-1/2" female NPT threads.
- Optional bronze or aluminum swivel joint and stainless steel hub assembly and riser are available.
- Optional rollers are available.
- Standard pressures to 600 psi (41 bar), available up to 1000 psi (69 bar) – must specify.
- Temperatures from -25°F to +250°F (-32°C to +121°C).



Standard configuration shown



Optional Aluminum Hand Cart

4300-AL mounting available.

PARTS DRAWING – ISO 111

Model Number	Hose Capacity of Reel feet m					Approx. Weight Crank Rewind lb. kg		Reel Dimensions*** in. mm						
	I.D. in. mm	Round Hose		Collapsible Hose		NET	SHIP	A	B	E	F	G	H	X
		1 25	1-1/2 38	1-1/2 38	1-3/4 44									
	O.D. in. mm	1-9/16 40	2-1/16 52	3/4x3 19x76	7/8x3-1/4 22x83									
3516-25-26	50	–	–	50	50	95	130	13	7.5	24.75	26	27.88	15.5	7.75
	15	–	–	15	15	43	59	330	191	629	660	708	394	197
3520-25-26	100	50	100	75	104	139	139	17	11.5	24.75	30	27.88	15.5	9
	30	15	30	23	47	63	63	432	292	629	762	708	394	229
3524-25-26	150	75	150	100	113	157	157	21	15.5	24.75	34	27.88	15.5	13
	46	23	46	30	51	71	71	533	394	629	864	708	394	330
3528-25-26	200	100	200	150	123	173	173	25.5	20	24.75	38.5	27.88	15.5	17.5
	61	30	61	46	56	78	78	648	508	629	978	708	394	445
3524-30-31	200	100	250	150	124	174	174	21	15.5	28.75	34	29.88	15.5	13
	61	30	76	46	56	79	79	533	394	730	864	759	394	330
3528-30-31	250	150	300	250	134	184	184	25.5	20	28.75	38.5	29.88	15.5	17.5
	76	46	91	76	61	83	83	648	508	730	978	759	394	445
3534-30-31	350	200	450	350	147	197	197	31.5	26	28.75	44.5	29.88	15.5	23.5
	107	61	137	107	67	89	89	800	660	730	1130	759	394	597
3530-33-34	400	250	450	350	138	188	188	27.5	22	31.75	40.5	32.38	16.5	19.5
	122	76	137	107	63	85	85	699	559	806	1029	822	419	495

Notes:

- Specifications subject to change.
- Upon request, reels can be supplied with drum lengths other than shown and with disc sizes in other diameters.
- Power rewind NOT available on these models.
- Dimension "F" is the overall length of standard model reels. For crank rewind models, 3-1/2" clearance is required to remove crank.

- Subtract 5" from "F" dimension for disc rewind models.
 - Finish:** Call factory for offshore/marine finish, available at extra cost. Refer to page 3.
 - Be sure to check dimensions and weights prior to ordering.**
- NOTICE:** A flexible connector must be used between the inlet pipe and the inlet swivel joint.
- *** X, Y indicate mounting holes. See page 5.

