

Series AVF

For use with 3mm to 9.2mm or larger broadcast fiber optic cable.

- Designed for Tactical Fiber and Hybrid Fiber cable types.
- Quality construction designed for harsh outdoor environments.
- Non-reflective black matte finish is standard.
- External and/or internal drum storage with protective rubber grommet for easy access to lead out cable, while keeping dirt and debris out.
- Crank handle permanently attached to disc.
- Equipped with cam-lock drag brake system

AVF-14

- Lightweight aluminum construction, under 10 lbs., for easy transport and handling.
- Modular frame style, handle and legs can be replaced in the event of damage.

AVF-18

- Durable aluminum/steel construction, under 25 lbs.
- Holds 1000 feet of SMPTE Cable.
- Frame style with clips allow multiple reels to be stacked.
- Optional heavy-duty, locking caster wheels (set includes 2 locking and 2 non-locking casters). Specify when ordering, add "C" to model number.
- Optional pull handle is available (Part No. 9949.0500). Specify when ordering.



AVF Series includes two durable rubber twist ties for cable ends.

Part No. 9949.0082

AVF-14

Standard configuration shown




Two AVF-18 reels stacked with pull handle and casters

AVF-18C



Standard configuration shown with optional casters

PARTS DRAWING – AVF-14–ISO 261, AVF-18–ISO 262

Model Number	Cable Capacity of Reel feet m							Approx. Weight without cable lb. kg		Reel Dimensions in. mm							
	Type O.D. (mm)	TAC 1 4.5	TAC 2 5	TAC 4 5.5	TAC 6 6	TAC 12 7	SMPTE 311M 9.2	NET	UPS/ FedEx. SHIP Wt.	A	B	C	D	E	F	G	H
AVF-14	1500	1300	1000	800	600	350	350	9.5	58*	9.50	6	6	13.5	14	13.25	18.25	7.94
	457	396	305	244	183	107	107	4.3	26	241	152	152	343	356	337	464	202
AVF-18	4000	3000	2500	2000	1600	1000	1000	24	80*	13	9	8	20	18.5	16.25	20.5**	10
	1219	914	762	610	488	305	305	11	36	330	229	203	508	470	413	521	254



AVF-14



AVF-18

Notes:

1. Specifications subject to change.
2. Be sure to check dimensions and weights prior to ordering.

*Dimensional weight applies when shipped as a parcel package (via FedEx or UPS Ground).

**For Model AVF-18 casters will add 4-3/4" to "G" dimension. When ordering casters add "C" to model number: AVF-18C.