

Model **LC16-10-11** Series **CR**

Model LC16-10-11 (Storage)

- Waterproof duplex receptacle for 3-pronged plug.
- Twist lock duplex is available.
- Adjustable cam-lock drag brake.
- Equipped with one durable rubber twist tie for cable ends.

Series CR (Live)

- Compact, lightweight, rugged construction.
- 3-conductor, 30-amp collector ring.
- 6 foot power source lead with 15-amp, 3-prong straight blade plug (optional twist lock is available).
- Adjustable cam-lock drag brake.

Rewind:

- Crank rewind permanent.



LC16-10-11

- Extension Cord
- Broadcast Cable

Series CR

- Industrial
- Broadcast
- Agricultural
- Fire and Rescue

PARTS DRAWING – MODEL LC16-10-11 – ISO 120; SERIES CR – ISO 156

Model Number	Cable Capacity of Reel feet m			Approx. Weight lb. kg		Reel Dimensions in. mm							
		Ga./No. of Conductors											
	O.D. in. mm	14/3 .53 14	12/3 .60 15	NET	SHIP	A	B	C	D	E	F	G	H
LC16-10-11	125	100	14	17*	11.25	7.5	4	11.62	10.75	13.75	14.75	6.88	
	38	30	6	8	286	190	102	295	273	349	375	175	
CR16-14-16	200	150	24	58*	9.25	7.5	6	15.5	14	14.5	18.5	8.88	
	61	46	11	26	235	190	152	394	356	368	470	226	
CR16-17-18	300	250	28	58*	9.25	7.5	6	15.5	16.5	14.5	18.5	8.88	
	91	76	13	26	235	190	152	394	419	368	470	226	

Notes:

1. Specifications subject to change.
 2. Be sure to check dimensions and weights prior to ordering.
- *Dimensional weight applies when shipped as a parcel package (via FedEx or UPS Ground).



LC16-10-11 includes one durable rubber twist tie for cable ends.

Part No. 9949.0082



Series CR

Optional 15-amp, 3-prong straight blade receptacle recessed in drum.
Part No. 9955.0090.

