

Series IV5000 | Single Wrap

• For Inverted Installation

To handle single 1-3/8" I.D. through 2" I.D. hose.

- Effortless and fast rewinding, wrapping, guiding of hose.
- Chain and sprocket drive powered by electric, hydraulic, compressed air motor.
- Auxiliary crank rewind is optional.
- 12 volt rewind; comet brake standard. Air brake optional.
- **5100 Series** - 90° ball bearing swivel joint, 1-1/2" female NPT threads, 2" Victaulic groove, flanged riser with 1-1/2" female NPT threads.
- **5200 Series** - 90° ball bearing swivel joint, 2" Victaulic groove, flanged riser with 2" female NPT threads.
- Inlet, hub assembly is aluminum.
- Joint and riser are ductile iron for petroleum fuel.
- Standard: pressures to 600 psi (41 bar).
- Temperatures from -30°F to +250°F (-34°C to +121°C).
- Standard with a reduction unit only. Electric clutch units optional.
- Consult factory for other pressures and temperatures.



Standard model shown with optional hose

PARTS DRAWING – ISO 197

Model Number For Power Rewind see Note 2	Hose Capacity of Reel feet m				Approx. Weight lb. kg		Reel Dimensions*** in. mm									
	I.D. in. mm	1-3/8 35	1-1/2 38	2 51	NET	SHIP	A	B	C	D	E	F POWER	G	H	X	Y
	O.D. in. mm	2.00 51	2.06 52	2.67 68												
IV5111-48-50-20	-	50	-	-	310	385	11.13	2.75	20	36	48	17.5	50	26	8.13	28
	-	15	-	-	141	175	283	70	508	914	1219	445	1270	660	296	711
IV5111-56-58-20	-	75	-	-	330	405	11.13	2.75	20	36	56	17.5	58	30	8.13	28
	-	23	-	-	150	184	283	70	508	914	1422	445	1473	762	206	711
IV5111-62-64-20	100	100	-	-	340	415	11.13	2.75	20	36	62	17.5	64	33	8.13	28
	30	30	-	-	154	188	283	70	508	914	1575	445	1626	838	206	711
IV5111-72-73-24	150	-	-	-	350	425	11.13	2.5	24	36	72	17.5	73	38	8.13	28
	46	-	-	-	159	193	283	64	610	914	1829	445	1854	965	206	711
IV5111-78-80-24	150	-	-	-	350	425	11.13	2.5	24	36	78	17.5	80	41	8.13	28
	46	-	-	-	159	193	283	64	610	914	1981	445	2032	1041	206	711
IV5218-56-58-20	-	-	50	-	370	445	12	3.75	20	36	56	19.25	58	41	9	28
	-	-	15	-	168	202	305	95	508	914	1422	489	1473	1041	229	711
IV5218-62-64-20	-	-	75	-	390	465	12	3.75	20	36	62	19.25	64	33	9	28
	-	-	23	-	177	211	305	95	508	914	1575	489	1626	838	229	711
IV5218-70-72-20	-	-	100	-	400	475	12	3.75	20	36	70	19.25	72	37	9	28
	-	-	30	-	181	215	305	95	508	914	1778	489	1829	940	229	711

Notes:

- Specifications subject to change.
 - When ordering power rewind models, prefix model number with:
 - A** = Air Rewind – Supplied with control valve and 18" air hose.
 - EP** = Electric Rewind (1/2 HP) – 12v and 24v DC rewind reels are supplied with switch and solenoid.
 - HD** = Hydraulic Rewind – Not supplied with control valve.
 - Be sure to check dimensions and weights prior to ordering.
- NOTICE:** A flexible connector must be used between the inlet pipe and the inlet swivel joint.
- *** X, Y indicate mounting holes.

