

Series **VAC-5000** | Single Wrap Reel

• Vacuum/Suction

To handle 2" through 4" I.D. hose

- Heavy-duty reel for longer lengths and large diameters of vacuum hose through 4".
- Choose gear driven crank rewind or chain and sprocket drive powered by an electric, hydraulic or compressed air motor.
- Standard: 90° ball bearing swivel joint with female NPT threads.

Single Wrap Configuration:

Use where width dimension is minimal, such as between cab and tank, mounted transverse to frame of truck. Provides effortless and fast rewinding and wrapping of hose. Easy access to hose from both sides of vehicle.



Standard configuration shown with Electric Rewind (EP) option (hose not included)

Model Number <small>For power rewind see Note 2</small>	Hose Capacity of Reel feet m				Approx. Weight lb. kg		Reel Dimensions*** In. mm									
	I.D. in. mm	2 51	3 76	4 102	NET	SHIP	A	B	C	D	E	F	G	H	X	Y
	O.D. in. mm	2.51 63.75	3.60 91.44	4.70 119.38												
VAC-5319-56-58-30	50	—	—	—	390	465	12.25	4.38	30	40	56	22	58	30	10.25	28
	15	—	—	—	177	211	311	111	762	1016	1422	559	1473	762	260	711
VAC-5319-64-66-30	75	—	—	—	410	485	12.25	4.38	30	40	64	22	66	34	10.25	28
	23	—	—	—	186	220	311	111	762	1016	1626	559	1676	864	260	711
VAC-5319-70-72-30	100	—	—	—	420	495	12.25	4.38	30	40	70	22	72	37	10.25	28
	30	—	—	—	191	225	311	111	762	1016	1778	559	1829	940	260	711
VAC-5420-62-64-30	—	50	—	—	415	490	13.50	5.63	30	40	62	25	64	33	11.50	28
	—	15	—	—	188	222	343	143	762	1016	1575	635	1626	838	292	711
VAC-5420-74-76-30	—	75	—	—	430	505	13.50	5.63	30	40	74	25	76	39	11.50	28
	—	23	—	—	195	229	343	143	762	1016	1880	635	1930	991	292	711
VAC-5420-80-82-30	—	100	—	—	438	513	13.50	5.63	30	40	80	25	82	42	11.50	28
	—	30	—	—	199	233	343	143	762	1016	2032	635	2083	1067	292	711
VAC-5420-68-70-30	—	—	50	—	422	497	13.50	5.63	30	40	68	25	70	36	11.50	28
	—	—	15	—	191	225	343	143	762	1016	1727	635	1778	914	292	711

Notes:

- Specifications subject to change.
 - When ordering power rewind models, prefix model number with:
 - A** = Air Rewind – Supplied with control valve and 18" air hose.
 - EP** = Electric Rewind (1/2 HP) – 12v and 24v DC rewind reels are supplied with switch and solenoid; 115v AC rewind reels are not supplied with switch but can be ordered separately.
 - HD** = Hydraulic Rewind – Not supplied with control valve.
 - Clutch/reduction unit available upon request.
 - Finish:** Refer to page 27.
 - Be sure to check dimensions and weights prior to ordering.**
- NOTICE:** A flexible connector must be used between the inlet pipe and the inlet swivel joint.
- *** X, Y indicate mounting holes which are 5/8" diameter.

