

Model Number For power rewind see Note 3	Hose Capacity of Reel feet m				Approx. Weight lb. kg		Reel Dimensions*** in. mm									
	I.D. in. mm	2 51	3 76	4 102	NET	SHIP	A	B	C	D	E	F	G	H	X	Y
	O.D. in. mm	2.51 64	3.60 91	4.70 119												
VAC-9334-33-34-20	50	–	–	–	160	230	26.25	20	20	31.50	31.75	36.25	33.88	18	18.75	27.75
	15	–	–	–	73	104	667	508	508	800	806	921	861	457	476	705
VAC-9340-33-34-20	75	–	–	–	200	270	32.25	26	20	31.50	31.75	42.25	33.88	18	24.75	27.75
	23	–	–	–	91	122	819	660	508	800	806	1073	861	457	629	705
VAC-9344-33-34-20	100	–	–	–	225	295	35.75	29.50	20	31.50	31.75	46.75	33.88	18	28.25	27.75
	30	–	–	–	102	133	908	749	508	800	806	1187	861	457	718	705
VAC-9330-39-40-20	50	–	–	–	188	258	21.75	15.50	20	40	39	31.75	40.38	20.88	14.25	37
	15	–	–	–	85	117	552	394	58	1016	991	806	1026	530	362	940
VAC-9332-39-40-20	75	–	–	–	200	270	23.75	17.50	20	40	39	33.75	40.38	20.88	16.25	37
	23	–	–	–	91	122	603	445	508	1016	991	857	1026	530	413	940
VAC-9334-39-40-20	100	–	–	–	212	282	26.25	20	20	40	39	36.25	40.38	20.88	18.75	37
	30	–	–	–	96	128	667	508	508	1016	991	921	1026	530	476	940
VAC-9332-45-46-20	150	–	–	–	350	420	23.75	17.5	20	46	45	33.75	46.38	23.88	16.25	43
	46	–	–	–	159	191	306	445	508	1168	1143	857	1178	607	413	1092
VAC-9336-45-46-20	200	–	–	–	375	445	28.25	22	20	46	45	38.25	46.38	23.88	20.75	43
	61	–	–	–	170	202	718	559	508	1168	1143	972	1178	607	527	1092
VAC-9340-45-46-20	250	–	–	–	400	470	32.25	26	20	46	45	42.25	46.38	23.88	24.75	43
	76	–	–	–	181	213	819	660	508	1168	1143	1073	1178	607	629	1092
VAC-9344-45-46-20	300	–	–	–	425	495	35.75	29.50	20	46	45	45.75	46.38	23.88	28.25	43
	91	–	–	–	192	225	908	748	508	1168	1143	1162	1178	607	718	1092
VAC-9438-39-40-24	–	50	–	–	250	320	30.25	24	24	40	39	41.5	41	21.50	22.75	37
	–	15	–	–	113	145	768	61	610	1016	991	1054	1041	546	578	940
VAC-9444-39-40-24	–	75	–	–	280	350	35.75	29.50	24	40	39	47	41	21.50	28.25	37
	–	23	–	–	127	159	908	749	610	1016	991	1194	1041	546	718	940
VAC-9434-48-50-24	–	100	–	–	270	340	26.25	20	24	49	48	37.50	50.50	26.50	18.75	46
	–	30	–	–	122	154	667	508	610	1245	1219	953	1283	673	476	1168
VAC-9448-48-50-24	–	150	50	–	320	390	40.25	34	24	49	48	51.50	50.50	26.50	32.75	46
	–	46	15	–	145	177	1022	864	610	1245	1219	1308	1283	673	832	1168
VAC-9444-56-58-24	–	200	75	–	375	445	35.75	29.50	24	57	56	47	58	30	28.25	54
	–	61	23	–	170	202	908	749	610	1448	1422	1194	1473	762	718	1371
VAC-9450-56-58-24	–	250	100	–	411	481	42.25	36	24	57	56	53.50	58	30	34.75	54
	–	76	30	–	186	218	1073	914	610	1448	1422	1359	1473	762	883	1371
VAC-9456-56-58-24	–	300	150	–	447	517	48.25	42	24	57	56	60.50	58	30	40.75	54
	–	91	46	–	203	235	1226	1066	610	1448	1422	1537	1473	762	1035	1371

Notes:

- Specifications subject to change.
 - Upon request, reels can be supplied with drum lengths other than shown and with disc sizes in other diameters.
 - When ordering power rewind models, prefix model number with:
A = Air Rewind – Supplied with control valve and 18" air hose.
EP = Electric Rewind (1/2 HP) – 12v and 24v DC rewind reels are supplied with switch and solenoid; 115v AC rewind reels are not supplied with switch but can be ordered separately.
HD = Hydraulic Rewind – Not supplied with control valve.
 - Clutch/reduction unit available upon request.
 - Finish:** Refer to page 27.
 - Be sure to check dimensions and weights prior to ordering.**
- NOTICE:** A flexible connector must be used between the inlet pipe and the inlet swivel joint.
- ***X, Y indicate mounting holes. See page 2.

